


1500 LT Mobile Safety Shower and Eye/Face Wash with Trailer



The unit is ex-proof (Atex) equipped with a pneumatic pump and 1500 liter water tank, sufficient for 15 minutes of water flow.

Water immersion heater is set at 25°C.

The mobile shower complies with both EN 15154 and ANSI/ISEA 7358.1-2014 standards.

Teknik Bilgiler

Standard 1500 lt Mobile Tank Showers
guarantee 15 minutes of water flow according
to the standard requirements in bellow
circumstances;

- 1. Without mains (water) supply connection
 - 2. In low water pressure

3. Interruption of flow in existing water supply connection

Ideal for applications where there is no mains water supply

1500 lt Water Tank on trailer

Trailer is equipped with signals, lights, oblong plate, parking brake etc, according to highway regulations

Suitable for temperatures -5 C° / +40 C°

Emergency Shower Material (Galvanized and Painted Steel or Stainless Steel)

Pneumatic Water Pump For Hazardous Areas

Electrical Pump For Non Hazardous Areas

50 lt 200 Bar air cylinder with pressure regulator (for operating of pneumatic pump) with its bracket & straps

Stabilizing legs

Bumper Bar

Visual water level indicator

Expansion Tank

Safety Signs and Green - White stripes

Available in green, yellow or white color

OPTIONS

- Ex-proof or Non Exproof Audible And Visual Alarm
- Ex-proof or Non Exproof chiller cooling unit
- Ex-proof or Non Exproof Lighting
 - Scald or Freeze
 Protection Valve
 - Testing Lever
- Eyewash Foot Treadle
 - Overhead ABS Shower Rose
 - 316 Stainless Steel Shower Material
 - Water Pressure Regulator

- Low Water Level

Alarm

- Visual Water Level

Indicator

- Visual Water

Temperature Gauge

- Water Immersion

Heater

- Water Low and High

Temperature Alarm







