

350 L TANK CAPACITY, PORTABLE, PRESSURIZED EMERGENCY SHOWER AND EYE / FACE WASHING UNIT, ISTECC© TYPE ESW-P

Article Number: 15039060 - 15039060-316



The pressure tanks of the units are manufactured and certified according to EN 13445: 2014 in accordance with the 2014/68 / EU directive. The unit CE marking and has proven safety.

Designed to use in areas where fixed emergency shower and eyewash fountains can not be installed and where there are various hazards at working areas or during temporary work.

Works with compressed air. It has two different entrances to fill water and air.

2" water filling plug is available.

There is a regulator for the flow regular at the outlet of the tank.

In the event of danger, the valve handle of the emergency shower or the valve handle of the eye / face wash unit is activated to ensure that clean water is sprayed.

According to customer request, the wheeled easy transport system can be included in the unit. Due to its compact structure, it does not occupy much space when not in use.

*After use, water and air filing operations are repeated and continuous usage is ensured.

The water temperature should be kept constant between 16-38 oC according to the requirements of the standard. Therefore, an EX-PROOF or NON-EXPROOF immersion heater can be added to the unit according to the customer's request.

The tank volume consists of 270 L water and 80 L air pressure and has a total capacity of 350 liters.

Standards



CE Mark



TS EN 13445:2014

The pressure tanks of the units are manufactured and certified according to EN 13445: 2014 in accordance with the 2014/68 / EU directive. The unit CE marking and has proven safety.

Designed to use in areas where fixed emergency shower and eyewash fountains can not be installed and where there are various hazards at working areas or during temporary work.

Works with compressed air. It has two different entrances to fill water and air.

2" water filling plug is available.

There is a regulator for the flow regular at the outlet of the tank.

In the event of danger, the valve handle of the emergency shower or the valve handle of the eye / face wash unit is activated to ensure that clean water is sprayed.

According to customer request, the wheeled easy transport system can be included in the unit. Due to its compact structure, it does not occupy much space when not in use.

*After use, water and air filing operations are repeated and continuous usage is ensured.

The water temperature should be kept constant between 16-38 oC according to the requirements of the standard. Therefore, an EX-PROOF or NON-EXPROOF immersion heater can be added to the unit according to the customer's request.

The tank volume consists of 270 L water and 80 L air pressure and has a total capacity of 350 liters.

General Features As per customer request;

*For emergency shower -Pull rod or push handle & foot treadle *For eye/face wash -Hand control or/and foot treadle

Water inlet pipes: 1"

Body pipes : 1 ¼"

Shower head and eyewash bowl diameter: 300 mm Shower materials can be produced as 304 K. Stainless Steel, 316 K. Stainless Steel or Galvanized steel according to customer request.

Pressure Information:

Max. Working pressure: 7 bar

Test pressure: 12 bar

Design pressure: 7 bar

OPTIONAL ACCESSORIES



The Protective Cover Against Harsh Weather Conditions