

3M™ Scott™ Promask Negative Pressure Full Face Mask

Article Number: 01010800

It is used as protective equipment by personnel working in environments containing harmful gases and/or particles that are hazardous to the eyes and respiratory system.

With its lightweight and ergonomic design, it can be used across a wide range of industries and industrial applications.

Equipped with a speech diaphragm and a panoramic visor, this multifunctional full-face mask provides exceptional comfort and protection against respiratory hazards.

It is manufactured in compliance with EN 136 Class 3 Standard and bears the CE Mark.



Standards



CE Mark

TECHNICAL DETAILS

Design:

- Suitable for single-filter use with EN 148-1 threaded connection.
- A dual-filter model is also available.
- Easy disinfection, decontamination, and maintenance.
- Special five-strap head harness for a secure fit.
- Weight: 525 g.
- Temperature range: -40°C to +100°C.
- Maximum heat resistance: +140°C.
- Resistant to wear and abrasion.
- Chemical resistant.

Materials:

- **Inner Mask:** Thermoplastic Elastomer (TPE)
- **Visor:** Polycarbonate (PC) and optional PC HC
- **Head Harness:** Natural Rubber (NR)
- **Valve Discs:** Silicone
- **Visor Frame:** Polybutylene Terephthalate (PBTE) (Thermoplastic Polyester)
- **Breathing Channel Body:** Polyamide (PA)
- **Speech Channel Body:** Polyamide (PA)
- **Speech Diaphragm Body:** Polyamide (PA)
- **Speech Channel Cover:** Polyamide (PA)
- **Inhalation Valve Seat (Inner Mask):** Polypropylene (PP)
- **Buckles:** Polyamide (PA)
- **Buckle Roller:** Polyacetal (POM)
- **Inhalation Valve Housing:** Silicone
- **Filter Thread Connector:** Polyamide (PA)

