



CLIMAX 419-E Welding Shield

Product Code: 07021850



(Wth Trigger) EN 175

Teknik Bilgiler

Double lenses which are clear lens and welding lens.

All tests were done.

Welding mask has EN 175 S protection level.

Lenses can be lifted up through trigger inside.

The Climax 419-E hand-held welding shield has been designed to provide effective protection against the radiation emitted during welding processes, as well as against incandescent particles released during such processes. The welding shield is also recommended for protection against the impact of low-energy, high-velocity particles. Due to its design and dimensions, the shield covers the entire face and neck. The lightweight design, ergonomic handle and optical quality of the glass allow the wearer to work comfortably and without inconvenience.

Description and Features

The Climax 419-E welding shield is manufactured of topquality, lightweight, highly resistant materials.

Body and handle

The body is made of fibreglass-reinforced polyester and has a flat, rectangular front with two flat sides and a semicircular upper surface. The body has a height of 386 mm and a variable width that ranges from 277 mm at the top to 227 mm at the bottom.

The handle system consists of a closed polypropylene handle with an ergonomic design for convenient use. The handle is joined to the inner face of the front by means of a guide system with anchoring stops. The entire system is made

of plastic.

Lens holder and lenses

The lens holder has a sliding design and comprises a rectangular edge conformed in the shield front and a rectangular frame fitted against the edge from the inside.

Both parts are secured with two metal bolts. The filter frame slides in the inner frame of the shield, actuated by means of a spring trigger in the handle.

This system allows the user to inspect the work without having to remove the shield from in front of his face,

such that protection
from flying particles
is provided at all times.

The lens assembly is
composed of a cover
lens, a filter lens and a
backing lens. All lenses
measure 110 x 55 mm
and are CE-certified.

The shield is
manufactured with a
standard filter lens
of shade 12, although a
wide range of other
filter shades are also
available (filter shade 8
to 14).

Packaging

Individual units in
plastic bag with
information leaflet.

Case of 50 units

Replacement Parts

The welding shield has
the following
replacement parts:

- Welding filter: shades
8 to 14. CE-certified.

- Cover lens (three
types are available):

- Cover lens no. 1: 2-
mm polycarbonate. CE-
certified.

- Cover lens no. 2: 3-
mm glass. CE-certified.

- Cover lens no. 3: 2-
mm glass. CE-certified.

- Filter lens holder

- Handle

CE Certification

Standards: EN 175:
1997

Directive 89/686/CEE

Regulatory agency no.

0159

Certificate no.

11226695

Applications

The Climax 419 welding shield is ideal for use in any welding process, as long as the proper filter lens shade is selected for the specific type of welding being performed. In each case, the welding shield offers full protection against the radiation emitted during the welding processes as well as against solid flying particles. In addition, the shield is also recommended for use

in processes where
there is a risk of
electrical discharges
(up to 500V and 4mA).

Technical Data

- Opacity of welding shields CONFORMS
- Increased mechanical strength CONFORMS
- Low-energy, high-velocity impact resistance CONFORMS
- Resistance to falls CONFORMS
- Electrical insulation (11.2 mA) CONFORMS
- Stability when exposed to water CONFORMS
- Resistance to flame/penetration of hot solids CONFORMS



SINCE
1979



9001:2015
CERTIFIED
COMPANY



Delivering Worldwide
70+ Countries and
Growing!