



Emergency Shower and Eye/Face Wash with Overhead 1500/2000 LT Water Tank ISTECH TYPE

ESW-OWT-1500-2000



Standard 1500/2000 lt Overhead Tank Showers guarantee 15 minutes of water flow according to the standard requirements in below circumstances;

1. Without mains (water) supply connection
2. In low water pressure
3. Interruption of flow in existing water supply connection

Different materials (Galvanized Steel, Stainless Steel, GRP) can be used in different system parts as optionally. You can customize your tank shower system by selection guide to integrate the system by chosen desired accessories and various system parts. Water Tanks are insulated. An integral immersion heater or a chiller unit can be added to the system with the options of ex-proof and non ex-proof, in order to keep the water temperature constant between 15-38 °C. Heating and cooling capacities may be changed according to customer requirements. Available in green, yellow or white color

Build and design your emergency tank showers in 3D according to the required climate & area classification!

Search “[Safety Shower Builder](#)” on Apple App Store or click on the link below and stay connected!

<https://apps.apple.com/tr/app/safety-shower-builder/id1536803797?l=tr>

Teknik Bilgiler

Standard 1500/2000 lt Overhead Tank Showers guarantee 15 minutes of water flow according to the standard requirements in bellow circumstances;

1. Without mains (water) supply connection
2. In low water pressure
3. Interruption of flow in existing water supply connection

Different materials (Galvanized Steel, Stainless Steel, GRP) can be used in different system parts as optionally.

You can customize your tank shower system by selection guide to integrate the system by chosen desired accessories and various system parts.

Water Tanks are insulated.

An integral immersion heater or a chiller unit can be added to the system with the options of ex-proof and non ex-proof, in order to keep the water temperature constant between 15-38 °C.

Heating and cooling capacities may be changed according to customer requirements.

Shower Head : 300 mm diameter

Eyewash Bowl : 300 mm diameter

Water Inlet : 1 ½" with flange

Water Outlet : 1 ¼"

Water Flow : Minimum 11,4 lt/min for eyewash

Minimum 75,7 lt/min for shower

Available in green, yellow or white color

OPTIONS

-

Ex-

proof

Or

Non

Ex-

proof

Audible

And

Visual

Alarm

-

Ex-

proof

Or
Non
Ex-
proof
chiller
cooling
unit
(for
hot
climates)

-

Water
Immersion
Heather
(for
cold
climates)

-

Scald
Or
Freeze
Protection

Valve

-

Testing
Lever

-

Eyebath

Foot

Treadle

-

Overhead

ABS

Shower

Rose

-

316

Stainless

Steel

Shower

Material

-

Overhead

Sun

Canopy

-

Low

Water

Level

Alarm

-

Side

&

Rear

Panelling

-

Spring

Loaded

Doors

-

Visual

Water

Level

Indicator

-

Visual

Water

Temperature

Gauge

-

Water

Low

And

High

Temperature

Alarm

-

Drain

Sump

and

Grating

-

Internal

or

External

lighting

-

Shower

activation

platform

-

Eyewash

may

be

located

internally

on

LHS

or

RHS

or
externally

-
LHS
or
RHS
when
viewed
in
front

-
Ex-
proof
space
heater

-
Ex-
proof
or
non
ex-
proof
flow
switch

-

Pressure
regulator

-

Stainless
steel
erecting
lugs

-

Thermo
mixing
valve

-

Wooden
Pallets

-

M20
Electrical
Box

-

Side
and
rear
panels
insulation

/
Water
Tank
insulation

-
Panic
Bar

/
Push
Bar

-
Platform
Activation

