



Emergency Shower and Eye/Face Wash with Overhead 630/1260 LT Water Tank ISTEK TYPE

ESW-OWT-630-1260

Standard 630/1620 lt Overhead Tank Showers supply 15 minutes flow rate according to the standard requirements on the condition of being connected to mains supply.

Different materials (Galvanized Steel, Stainless Steel, GRP) can be used in different system parts as optionally. You can customize your tank shower system by selection guide to integrate the system by chosen desired accessories and various system parts.

Water Tanks are insulated. An integral immersion heater or a chiller unit can be added to the system with the options of ex-proof and non ex-proof, in order to keep the water temperature constant between 15-38 °C. Heating and cooling capacities may be changed according to customer requirements.

Build and design your emergency tank showers in 3D according to the required climate & area classification!

Search "Safety Shower Builder" on Apple App Store or click on the link below and stay connected!

<https://apps.apple.com/tr/app/safety-shower-builder/id1536803797?l=tr>



Standard 630/1260 lt Overhead Tank Showers supply 15 minutes flow rate according to the standard requirements on the condition of being connected to mains supply.

Different materials (Galvanized Steel, Stainless Steel, GRP) can be used in different system parts as optionally.

You can customize your tank shower system by selection guide to integrate the system by chosen desired accessories and various system parts.

Water Tanks are insulated.

An integral immersion heater or a chiller unit can be added to the system with the options of ex-proof and non ex-proof, in order to keep the water temperature constant between 15-38 °C.

Heating and cooling capacities may be changed according to customer requirements.

Shower Head : 300 mm diameter

Eyewash Bowl : 300 mm diameter

Water Inlet : 1 ½" with flange

Water Outlet : 1 ¼"

Water Flow : Minimum 11,4 lt/min for eyewash

Minimum 75,7 lt/min for shower

Available in green, yellow or white color

OPTIONS

- Ex-proof

Or Non Ex-

proof

Audible

And Visual

Alarm

- Ex-proof

Or Non Ex-

proof

chiller

cooling unit

(for hot

climates)

- Water

Immersion

Heather

(for cold

climates)

- Scald Or

Freeze

Protection

Valve

- Testing

Lever

- Eyebath

Foot

Treadle

- Overhead

ABS

Shower

Rose

- 316

Stainless

Steel

Shower

Material

- Overhead

Sun

Canopy

- Low

Water Level

Alarm

- Side &

Rear

Panelling

- Spring

Loaded

Doors

- Visual

Water Level

Indicator

- Visual

Water

Temperature

Gauge

- Water

Low And

High

Temperature

Alarm

-

Drain

Sump

and

Grating

-

Internal

or

External

lighting

-

Shower

activation

platform

-

Eyewash

may

be

located

internally

on

LHS

or

RHS

or

externally

- LHS

or

RHS

when

viewed

in

front

- Ex-

proof

space

heater

- Ex-
proof
or
non
ex-
proof
flow
switch

-
Pressure
regulator

-
Stainless
steel
erecting
lugs

-
Thermo
mixing
valve

-
Wooden
Pallets

- M20
Electrical

Box
- Side
and
rear
panels
insulation
/
Water
Tank
insulation
-
Panic
Bar /
Push
Bar
-
Platform
Activation

