

## EUREKA 15-4AMPVIB (PERIODICALLY CHANGING VIBRATION) PROTECTIVE GLOVES

CE marked and certified in accordance with Regulation (EU) 2016/425 Personal Protective Equipment (PPE).

Certified according to the EN 388 "Protective gloves against mechanical risks" standard.

Abrasion, cut, tear, perforation values are 4X41F.

Certified according to the EN ISO 10819:2013+A1:2019 'Mechanical vibration and shock. hand-arm vibration. Measurement and evaluation of the vibration transmissibility of gloves at the palm of the hand standad. TRM = 0,76 TRH = 0,67

ANSI cut level is A6.

This glove is suitable for use when handling high frequency tools.(>~200 Hz)



### Standards



CE Mark



Category II



ANSI CUT LEVEL A6



EN388 4X41F

## TECHNICAL DETAILS

Protective gloves against vibration have recently become very important in reducing the hand-arm vibration syndrome that may occur as a result of vibration.

The vibrations are generated by the machine motor (rpm) or some very high frequency transient vibrating tools used.

Vibration spread properties according to the tools used are given in the table below ;

Tool Used	Flexibility	Amplitude	Vibration	Non-Periodic Vibration
Rivet guns, Impact wrenches, Impact hammers	SARI	SARI	SARI	SARI
High speed multiple tools	SARI	SARI	SARI	SARI
Angle grinders	SARI	SARI	SARI	SARI
Sanding Machines and Grinders	SARI	SARI	SARI	SARI
Nutrunners	SARI	SARI	SARI	SARI
Mower, Hedge trimmer, Leaf blower	SARI	SARI	SARI	SARI
Circular and Jig Saws	SARI	SAR I	SARI	SARI

Green: Low, Yellow: medium, Red: High

Frequency = Oscillations per second

RPM = Revolutions per minute

100 Hz = 6000 rpm, 500 Hz = 30000 rpm

Transient Vibration = High frequency is the best measure of short duration acceleration, velocity change per second and vibration strength



İvedik OSB Mh. 2269. Cd. No:42 PK.06374 Yenimahalle / ANKARA



0312 384 13 00



info@ist.com.tr