

Freeze Proof Cable Heated and Insulated Emergency Shower and Eye/Face Wash ISTECH Type ES-ICH & ESW-ICH

Article Number: 15036100 - 15036100-316 - 15036100-EX
- 15036100-EX-316 - 15036150 - 15036150-EX - 15036100
(PMŞ) - 15036150 (PMŞ)

(OUTDOOR USE FOR COLD CLIMATES)

P/N : 15026100 / 15036100 (Stainless Steel)

P/N : 15026150 / 15036150 (Galvanized Steel)

Protective against Freezing with cable heating (10-15 W/m, AC 230 V, Ex-Proof) and complete insulating system Suitable for extreme cold weather conditions Green color is standard. Beige and black color is available.

ISTECH®
SHOWERS & EYEBATHS



Standards



CE Mark



Ex-Proof (ATEX)



EAC/GOST-R



Meets requirements
of ANSI standard.



EN 15154-1



EN 15154-2



EAC

TECHNICAL DETAILS

Push Handle Control for Eyewash, Pull Rod Control for Shower

Available for hazardous and non-hazardous areas

10-15 W/m, AC 230 V, Ex-Proof Cable Heating with Insulation for freeze protection

Shower Material : 304 Stainless Steel or Galvanized Steel

Pipes : 1 1/4" Stainless Steel or Galvanized Steel

Shower Head and Eyewash Bowl : 300 mm diameter, Stainless Steel or Galvanized Steel

Water Inlet : 1"


Water Outlet : 1 1/4 "

Water Flow : Minimum 11.4 lt/min for eyewash
Minimum 75.7 lt/min for shower

OPTIONS

- Ex-proof Mechanical Thermostat
- Ex-proof or non Ex-proof Audible and Visual Alarm
 - Scald Protection Valve
- Shower activation Platform
 - Eyewash Foot Treadle
- Overhead ABS shower Rose
- 316 Stainless Steel Shower Material
 - Flow Switch


OPTIONAL ACCESSORIES




NON-EXPROOF

EXP-PROOF

Flow Switch




Freeze Protection Valve




NON-EXPROOF

EXP-PROOF

Electrical Connection Box




The Flanged Water Inlet




NON-EXPROOF

EXP-PROOF

Visual Alarm for Shower



The GRP Sunshade



The GRP Grate and Water Collection Basin

NON-EXPLOOF



Internal and External Lighting

EXPLOOF



Scald Protection Valve



The Water Pressure Gauge



The Hot & Cold Water Mixing Valve



The Water Temperature Indicator



The Foot Pedal Controller



The Foot Pedal Controller



The E-GSM Warning Device



The Rubber Dust Cover



The Compliance Test Kit



The Trigger Valve



The Proximity & Motion Sensor



Pressure Regulator



The Dirt Catcher Filter



The Three-Sided Enclosed Cabin

