

## Freeze-Proof Combined Unit, ISTEK Typ ESW, Hand Operated

**Article Number:** 15039570

**ISTEK®**  
SHOWERS & EYEBATHS



EXPROOF and NON-EXPROOF. In order to provide a safe working environment in terms of occupational health and safety, it has been produced in accordance with the requirements of ANSI Z358.1 and EN 15154-1-2 standards and has certificates.

According to the standards, it has to provide an uninterrupted water flow of 11.4 l per minute for 75.7 l eye / face washing fountain per minute for emergency shower for 15 minutes, and it provides this by connecting to a water network.

Optionally, shower systems and parts can be produced from different materials.

The water temperature should be kept constant between 16-38 ° C according to the requirements of the standard. For this purpose, the Thermomixer, which provides the ideal temperature by mixing the water coming from the hot and cold water sources feeding the water network, can also be included in the system.



### Standards



CE Mark



ANSI / ISEA Z358.1-  
2014



ANSI / ISEA Z358.1-  
2014 (Plumbing)



EAC/GOST-R



Meets requirements  
of ANSI standard.



EN 15154-1



EN 15154-2



EAC

# TECHNICAL DETAILS

---

## GENERAL FEATURES

Eye Baths with moving and filtered sprayer ends.

Fresh and waste water pipes in same profile.

Simple and compact structure , electrostatic painted or rustproof surface.

Wide range of versions according to customer needs.

Easy and practical assembly.



İvedik OSB Mh. 2269. Cd. No:42 PK.06374 Yenimahalle / ANKARA



0312 384 13 00



info@ist.com.tr