

Wolf® Ex-proof TR-30+ 2 batteries ,Right Angle ATEX, T4, LED

Article Number: 08010451

The Wolf TR-30 is a high-efficiency LED flashlight featuring a **90-degree right-angle** body design, specifically engineered for hands-free operations in hazardous areas. Offered by **IST Safety Ltd, the official distributor of Wolf**, this model is a primary choice for technical personnel due to its robust polymer body and integrated clip that allows for secure attachment to protective gear.



The device is fully certified for both industrial hazardous areas (Zone 1/21) and underground mines (**I M2 Mining**). Utilizing next-generation LED technology, it delivers a powerful 130-lumen beam while providing up to 27 hours of continuous illumination on just two D-cell batteries. This exceptional runtime significantly reduces operational costs during long shifts.

Usage Areas

- **Mining:** Underground mine operations, firedamp risk areas, and tunnel inspections.
- **Fire & Rescue:** Hands-free illumination by clipping the right-angle head onto protective suits.
- **Oil & Gas:** Refineries, drilling platforms, and confined space entries.
- **Marine:** Vessel maintenance, tank inspections, and hazardous cargo operations.

Certification & Compliance:

- Suitable for use in Zones 1 & 2, Zones 21 & 22 (dust)
- Dust Group IIIA,IIIB
- Gas Groups IIA, IIB,IIC
- Temperature Class: T4
- Complies with EN IEC 60079-0,EN 60079-11 standards
- EX I M2/II 2GD Ex ib I Mb/IIC T4 Gb
Ex ib IIIB T130°C Db

Technical Specifications:

- **Light Source:** Torch LED Module, Up to 130 lm

- **Light Source Output (Lumens):** Up to 130 lm
- **Brightness Duration:** Up to 14 hours to low power indicator ,Up to 17 hours total
- **Body Material/Lens:** Impact Resistant Thermoplastic, Chemical Resistant, Static Dissipative
- **Power Source:** It is powered by 2 x 1.5 V batteries
- **Ingress Protection:**IP67
- **Weight (inc. cells):** Approximately 0.500 kg

Warranty and Technical Support

- **Warranty:** 2-year manufacturer's warranty.
- **Official Support:** Original spare parts and professional technical service are provided through IST Safety Ltd, the official distributor of Wolf in Turkey.

Standards



Ex-Proof (ATEX)



IECEX



CE 0598



LR Certificate

TECHNICAL DETAILS

MODEL	TR-30+	TS-30+	TR-35+	TS-35+
PRODUCT DESCRIPTION	Primary Cell LED Right Angle or Straight Safety Torch			
	Right Angle Zone 1 & 21	Straight Zone 1 & 21	Right Angle Zone 0 & 21	Straight Zone 0 & 21
CODE	I M2/II 2GD Ex ib I Mb/IIC T4 Gb Ex ib IIIB T130°C Db	I M2/II 2GD Ex ib I Mb/IIC T4 Gb Ex ib IIIB T130°C Db	I M1/II 1G2D Ex ia I Ma/IIC T4 Ga Ex ib IIIB T130°C Db	I M1/II 1G2D Ex ia I Ma/IIC T4 Ga Ex ib IIIB T130°C Db

TYPE OF PROTECTION		'ib' intrinsic safety		'ia' intrinsic safety	
AREA OF CLASS(GAS)		Zones 1 & 2 Gas Groups IIA, IIB and IIC		Zones 0, 1 & 2 Gas Groups IIA, IIB and IIC	
TEMPERATURE CLASSIFICATION(GAS)		T4			
AREA OF CLASSIFICATION (DUST)		Zones 21 & 22 Dust Groups IIIA and IIIB		Zones 21 & 22 Dust Groups IIIA and IIIB	
MAX. SURFACE TEMP. (DUST)		T130°C			
AMBIENT TEMPERATURE (GAS)		-30° to +40 / 55°C	-20°C to +40 / 55°C	-30° to +40 / 55°C	-20° to +40 / 55°C
		Maximum ambient temperature is for use only with certain specified cells, as per product instructions.			
CERTIFICATE		ATEX Baseefa / 07ATEX0091X IECEX BAS 06.0089X / BAS21UKEX0437			
ENCLOSURE		Impact Resistant Thermoplastic, Chemical Resistant, Static Dissipative			
LENS		Toughened Glass 4mm			
BEAM TYPE		Medium Spot with Wide-Angle Flood of Fringe Light			
LIGHT SOURCE	PART NO	TP-300			
	POWER	Torch LED Module			
	OUTPUT	Up to 130 lm			
	LIFE	25,000hrs+ (Fitted for Life)			

POWER SOURCE	PART NO.	2 x H-20 (2 x LR-20 Cell suitable for 55° Maximum Ambient Temperature) (Batteries not supplied with torch)			
	TYPE	LR20 Primary Cells to IEC60086			
	POWER	2 x 1.5v			
LOW BATTERY INDICATOR		Yes			
LIGHT DURATION		Up to 14 hours to low power indicator Up to 17 hours total			
INGRESS PROTECTION		IP67			
WEIGHT(INC.CELLS)		0.500kg	0.475kg	0.500kg	0.475kg

What is ATEX Lighting?

[What is ATEX and what does exproof mean?](#) The **ATEX directive** is a set of European Union standards that define the safety requirements for equipment used in hazardous areas with explosive atmospheres. **Exproof** (Explosion-proof) refers to protection methods designed to prevent explosions by inhibiting the formation of sparks or electrical arcs in environments containing flammable gases, dust, or vapors. To ensure life and property safety in industrial facilities, the use of **ATEX-certified exproof devices** is a legal requirement.

What is ATEX Zone Classification?

[ATEX Zone coding](#) is a technical classification based on the frequency and duration of the occurrence of an explosive atmosphere in a given area. While the terms **Zone 0, 1, and 2** are used for risks originating from gas, vapor, and mist; the codes **Zone 20, 21, and 22** are designated for environments containing combustible dust. This classification is a legal standard that determines the required Equipment Protection Level (EPL) for devices. Accurate zone identification both optimizes operational costs and minimizes occupational safety risks.

What is IECEx Certification? How Does it Differ from ATEX?

In addition to ATEX certification, some projects may also require the IECEx Certification System (International Electrotechnical Commission Explosive Atmospheres System) certification. IECEx is an internationally recognized conformity assessment system for equipment intended for use in explosive atmospheres.

While ATEX is a European Union directive and a legal requirement within the European market, IECEx is a globally accepted certification system, widely preferred in regions such as the Middle East, Asia, and Australia.

From a technical perspective, both ATEX and IECEx are based on similar standards (e.g., the EN/IEC 60079 series). However:

- ATEX is a mandatory legal directive, whereas
- IECEx is an international certification system (voluntary, but widely required)

Therefore, while ATEX certification may be sufficient for certain projects, international tenders or critical industries such as oil & gas often prefer or require products that are certified to both ATEX and IECEx standards.

The appropriate certification should be determined based on the project location, client requirements, and application area.



İvedik OSB Mh. 2269. Cd. No:42 PK.06374 Yenimahalle /ANKARA



0312 384 13 00



info@ist.com.tr