



## Wolf LinkEx™ Tank Lighting Kit



- ATEX and IECEx Certified
- Approved for explosive Gas and Dust atmospheres
- Ultra bright, high power, low maintenance LED 'Fitted for Life'
- SOVI™ (Safe and Optimal Voltage Indicator) - on LinkEx™ LED Temporary Luminaires (including Emergency) and the LinkEx™ WF-300XL & WF-250XL Floodlite - for maximum safety
- Powers up to 8 LED Luminaires
- Emergency luminaires with backup battery supply for extra safety
- Fitted with ATX plugs and sockets
- Low and easy maintenance
- Robust, durable and lightweight construction
- Quick and easy installation over a large area
- Low power consumption
- Wide range of accessories

### Teknik Bilgiler

Product Reference	Transformer		Kit	
	Material Voltage Model	VA	Temp. Class & Ambient (°C)	Code

4 x LX-400 180°  Cabling (per light): 20m SY 2.5mm <sup>2</sup>	GRP 110V LL-114/T4	250	T4 -20°C to +50°C	LX- 175/T4
	SS 110V LL-133/T4	250	T4 -20°C to +55°C	LX- 185/T4
	GRP 230 LL-214/T4	250	T4 -20°C to +55°C	LX- 275/T4
	SS 230V LL-233/T4	250	T4 -20°C to +55°C	LX- 285/T4
4 x LX-400E (EMERGENCY)  Cabling (per light): 20m SY 2.5mm <sup>2</sup>	GRP 110V LL-114/T4	250	T4 -20°C to +55°C	LX- 145/T4
	SS 110V LL-133/T4	250	T4 -20°C to +55°C	LX- 165/T4
	GRP 230 LL-214/T4	250	T4 -20°C to +55°C	LX- 245/T4
	SS 230V LL-233/T4	250	T4 -20°C to +55°C	LX- 265/T4
3 x LX-400 180° + 1 x LX-400E  Cabling (per light): 20m SY 2.5mm <sup>2</sup>	GRP 110V LL-114/T	250	T4 -20°C to +55°C	LX- 146/T4
	SS 110V LL-133/T4	250	T4 -20°C to +55°C	LX- 166/T4
	GRP 230 LL-214/T4	250	T4 -20°C to +55°C	LX- 246/T4

SS 230V LL-233/T4	250	T4 - 20°C to +55°C	LX-266/T4	
3 x LX-400 180° + 1x 360°  Cabling (per light): 20m SY 2.5mm <sup>2</sup>	GRP 110V LL-114/T4	250	T4 -20°C to +55°C	LX- 176/T4
	SS 110V LL-133/T4	250	T4 -20°C to +55°C	LX- 186/T4
	GRP 230 LL-214/T4	250	T4 -20°C to +55°C	LX- 276/T4
	SS 230V LL-233/T4	250	T4 -20°C to +55°C	LX- 286/T4
2 x LX-400 180° + 2 x WF- 300XL  Cabling (per light): 20m SY 2.5mm <sup>2</sup> (LX) 20m SY 2.5mm <sup>2</sup> (WF)	GRP 110V LL-114/T3	320	T3 -20°C to +50°C	LX- 137/T3
	SS 110V LL-133/T3	320	T3 -20°C to +42°C	LX- 157/T3
	GRP 230 LL-214/T3	320	T3 -20°C to +50°C	LX- 237/T3
	SS 230V LL-133/T3	320	T3 -20°C to +42°C	LX- 257/T3
4 x WF-300XL  Cabling (per light): 20m SY 2.5mm <sup>2</sup>	GRP 110V LL-114/T3	400	T3 -20°C to +35°C	LL-135/T3

SS 110V LL-133/T3	400	T3 - 20°C to +30°C	LL-155/T3	
GRP 230 LL-214/T3	400	T3 - 20°C to +35°C	LL-235/T3	
SS 230V LL-233/T3	400	T3 - 20°C to +30°C	LL-255/T3	
4 x WF-250XL  Cabling (per light): 20m SY 2.5mm <sup>2</sup>	GRP 110V (LL-114/T4)	250	T4 -20°C to +55°C	LX- 139/T4
	SS-110V (LL-133/T4)	250	T4 -20°C to +55°C	LX- 159/T4
	GRP 230V (LL-214/T4)	250	T4 -20°C to +55°C	LX- 239/T4
	SS 230V (LL-233/T4)	250	T4 -20°C to +55°C	LX- 259/T4
8 x LX-400 180° (2 x chains x4 linked)  Cabling (per light): 5m light SY 2.5mm <sup>2</sup>	GRP 110V LL-114/T3	400	T3 -20°C to +35°C	LX- 177/T3
	SS 110V LL-133/T3	400	T3 -20°C to +30°C	LX- 187/T3

GRP 230 LL-214/T3	400	T3 - 20°C to +35°C	LX-277/T3	
SS 230V LL-233/T3	400	T3 - 20°C to +30°C	LX-287/T3	
8 x LX-400E (EMERGENCY) (2 x chains x4 linked)  Cabling (per light): 5m light SY 2.5mm <sup>2</sup>	GRP 110V LL-114/T3	400	T3 -20°C to +35°C	LX- 147/T3
	SS 110V LL-133/T3	400	T3 -20°C to +30°C	LX- 167/T3
	GRP 230 LL-214/T3	400	T3 -20°C to +35°C	LX- 247/T3
	SS 230V LL-233/T3	400	T3 -20°C to +30°C	LX- 267/T3



SINCE  
1979



9001:2015  
CERTIFIED  
COMPANY



Delivering Worldwide  
70+ Countries and  
Growing!