



Wolf M-85 Midi LED Safety Torches

Product Code: 08011600

EN 60529:1992 standard IP 67 water and dust protection. ATEX certificate.



Design:

Suitable for use in Zones 0, 1 & 2 Gas Group IIA, IIB, T3/T4 temperature range.

High-power LED type source provides wide-angle continuous illumination more than 7 hours with fullbrightness.

Operates with 4 x AA 1.5 volt alkaline battery.

Weight is appr. 190 kgs.

Teknik Bilgiler

Product Reference	M-85
Product Description	ATEX Midi Safety Torch with LED Primary Cell Powered
Code	Industrial
	II 1G Ex ia op is IIC T3/T4 Ga IP67 II 1D Ex ia op is IIIB T200°C Da

Mining	I M1 Ex ia I Ma IP67	
Type of Protection	'ia' Intrinsic Safety	
Area of Classification (Gas)	Zone 0, Gas Group IIC	
Temp. Classification (Gas)	T3/T4	
Area of Classification (Dust)	Zone 20 Dust Groups IIIA and IIIB	
Max Surface Temperature (Dust)	200°C	
Ambient temperature	-40°C to +40°C	
Certificate	Baseefa11ATEX0236X / IECEx BAS 11.0116X	
Enclosure	Impact Resistant Thermoplastic	
Lens	Polycarbonate, Impact Resistant	
Beam Type	Narrow Spot with Wide Angle Fringe Light	
Light Source:	Type	High Power LED
	Output	Up to 210 lm
	Life	25,000+ hours (fitted for life)
Power Source:	Part Number	TP-295 (4 x LR6 Cells)

Battery Type	LR6 Primary Cells, to IEC 60086, Alkaline AA
Volts	4 x 1.5v
Light Duration	Up to 7 hours
Ingress Protection	IP67
Weight (incl. battery)	0.190Kg



Delivering Worldwide
70+ Countries and
Growing!