



Wolf R-50 Rechargeable Safety Torches

Product Code: 08010453

Suitable for use in Zones 1 & 2 Gas Group IIA, IIB, IIC , T4 temperature range.



Powerful LED type source provides 3 watt power high intensity illumination up to 3.5 / 6.5 hours.

Polycarbonate lens, thermoplastic, resistant body.

Lithium-Ion battery is charged about in 1.5 - 3 hours, can be charged and used more than 500 times.

Weight is appr. 375 grams.

EN 60529:1992 standard IP 67 water and dust protection.

II 2GD Ex ib IIC T4 tD A21 IP67 T85°C ATEX certificate.



CE Mark



Ex-Proof (ATEX)

TECHNICAL INFORMATION

Suitable for use in Zones 1 & 2 Gas Group IIA, IIB, IIC , T4 temperature range.

Powerful LED type source provides 3 watt power high intensity illumination up to 3.5 / 6.5 hours.

Polycarbonate lens, thermoplastic, resistant body.

Lithium-Ion battery is charged about in 1.5 - 3 hours, can be charged and used more than 500 times.

Weight is appr. 375 grams.

EN 60529:1992 standard IP 67 water and dust protection.

II 2GD Ex ib IIC T4 tD A21 IP67 T85°C ATEX certificate.



SINCE
1979



9001:2015
CERTIFIED
COMPANY



Delivering Worldwide
70+ Countries and
Growing!