
Wolf® Rechargeable Torch Charger Bank



- It supports both 100-254VAC and 12-24VDC vehicle charging systems.
- Allows convenient recharging and storage for the Wolf R-50 and R-55 Rechargeable Torches.
- Designed for safe area indoor and internal vehicle
- Can be mounted in various orientations.
- Exceeds EN1789:2000 6.3.5 standards, providing torch retention in shock conditions up to 40G (EN1789 requires 15G).
- Quick and easy installation.
- Adjustable mounting points for added flexibility in tight spaces.
- Quick and tidy wiring and cable management.
- Aluminium and steel-plated fixings for long durability.
- Fast charging: 90% charge in 1.5 hours, full charge in 3 hours.



RECHARGEABLE TORCH CHARGER BANK

Product Reference	RC-203	RC-204	RC-205	RC-303	RC-304	RC-305
Product Description	Rechargeable Torch Charger Bank					
For No. Torches	3	4	5	3	4	5
Apparatus Standards	BS EN 1789:2000 Medical Vehicles and Equipment 6.3.5					
Insulation Class	III					
Enclosure	Thermoplastic					
Input Voltage	12-24VDC			100-254VAC		
Peak Current	4.5A	6A	7.5A	4.5A	6A	7.5A
Recharge Time	90% in 1.5hrs / Full Charge 3hrs					
Ingress Protection	IP20					
Weight	1.3kg	1.7kg	2.1kg	2.2kg	2.6kg	3.0kg
Mounting	Wall Mounted / Flat Surface / Bulk Head					
Compatible Torch	R-50 / R-55					



