



## Wolf TR 24B-26B Series Safety Torches

**Product Code: 08010200**

WOLF TR-24B T6 Series Safety Torches (2 Batteries-Straight Angle) P/N : 08010200

WOLF TR-26B T6 Series Safety Torches (2 Batteries-Right Angle) P/N : 08010400



**TR-24B** = II 2GD Ex eb ib IIB T4  
Gb

Ex tb IIIC T95°C Db

(-20°C ≤ Ta ≤ +40/55°C)

**TR-26B** = II 2GD  
Ex eb ib IIB T6  
Gb

Ex tb IIIC T65°C  
Db

(-20°C ≤ Ta ≤  
+40°C)

ATEX  
certification.

EN 60529:1992 standard IP 67 water and dust protection.

### **Design :**

Suitable for use in Zones 1 & 2 Gas Groups IIB T6 (TR-26B) and T4 (TR-24B) temperature range.

Suitable for use in Zones 21 & 22 Gas Groups IIC

Vacuum filament type source provides 1.7 watt illumination.

Shielded unbreakable reinforced glass lens, impact resistant thermoplastic, electrostatic housing.

Operates with 2 pcs 1,5 V. batteries and provides illumination more than 5 hours.

Weight is appr. 150 / 190 grams.



CE Mark



Ex-Proof (ATEX)

## TECHNICAL INFORMATION

---

WOLF TR-24B T6 Series Safety Torches (2 Batteries-Straight Angle) P/N : 08010200

WOLF TR-26B T6 Series Safety Torches (2 Batteries-Right Angle) P/N : 08010400

**TR-24B** = II 2GD Ex eb ib IIB T4 Gb

Ex tb IIIC T95°C Db

(-20°C ≤ Ta ≤ +40/55°C)

**TR-26B** = II 2GD Ex eb ib  
IIB T6 Gb

Ex tb IIIC T65°C Db

(-20°C ≤ Ta ≤ +40°C)

ATEX  
certification.

EN 60529:1992 standard IP 67 water and dust protection.

### Design :

Suitable for use in Zones 1 & 2 Gas Groups IIB T6 (TR-26B) and T4 (TR-24B) temperature range.

Suitable for use in Zones 21 & 22 Gas Groups IIC

Vacuum filament type source provides 1.7 watt illumination.

Shielded unbreakable reinforced glass lens, impact resistant thermoplastic, electrostatic housing.

Operates with 2 pcs 1,5 V. batteries and provides illumination more than 5 hours.

Weight is appr. 150 / 190 grams.

