



## Wolf TR-40 Safety LED Torches

**Product Code: 08010440**

### **WOLF TR-40 Safety LED Torches (Yellow)**



Suitable for use in Zones 1& 2 Gas Group IIA, IIB, IIC ,T3-T4 temperature ranges.

High powered LED type source provides continuous illumination with full brightness for 7.5 hours, and wide-angle 1.4 watt illumination up to 32 hours.

Shielded unbreakable polycarbonate lens, impact resistant thermoplastic, electrostatic housing .

Operates with 4 pcs AA 1.5 volt alkali batteries.

Weight is appr. 350 grams.

EN 60529:1992 standard IP 67 water and dust protection.

EX II 1 G Ex ia IIC T4/T3 IP67 ATEX certificate.

### **WOLF TR-45 Safety LED Torches (Black)**

Suitable for use in Zones 0, 1& 2 Gas Group IIA, IIB, IIC, T3-T4 temperature ranges.

High powered LED type source provides continuous illumination with full brightness for 7.5 hours, and wide-angle 1.4 watt illumination up to 32 hours.

Shielded unbreakable polycarbonate lens, impact resistant thermoplastic, electrostatic housing .

Operates with 4 pcs AA 1.5 volt  
alkali batteries.

Weight is appr. 350 grams.

EN 60529:1992 standard IP 67 water and dust protection.

EX II 1 G Ex ia IIC T4/T3 IP67 ATEX certificate.



CE Mark



Ex-Proof (ATEX)

## TECHNICAL INFORMATION

---

### **WOLF TR-40 Safety LED Torches (Yellow)**

Suitable for use in Zones 1& 2 Gas Group IIA, IIB, IIC ,T3-T4 temperature ranges.

High powered LED type source provides continuous illumination with full brightness for 7.5 hours, and wide-angle 1.4 watt illumination up to 32 hours.

Shielded unbreakable polycarbonate lens, impact resistant thermoplastic, electrostatic housing .

Operates with 4 pcs AA 1.5 volt alkali batteries.

Weight is appr. 350 grams.

EN 60529:1992 standard IP 67 water and dust protection.

EX II 1 G Ex ia IIC T4/T3 IP67 ATEX certificate.

### **WOLF TR-45 Safety LED Torches (Black)**

Suitable for use in Zones 0, 1& 2 Gas Group IIA, IIB, IIC, T3-T4 temperature ranges.

High powered LED type source provides continuous illumination with full brightness for 7.5 hours, and wide-angle 1.4 watt illumination up to 32 hours.

Shielded unbreakable polycarbonate lens, impact resistant thermoplastic, electrostatic housing .

Operates with 4 pcs AA 1.5 volt alkali batteries.

Weight is appr. 350 grams.

EN 60529:1992 standard IP 67 water and dust protection.

EX II 1 G Ex ia IIC T4/T3 IP67 ATEX certificate.



SINCE  
1979



9001:2015  
CERTIFIED  
COMPANY



Delivering Worldwide  
70+ Countries and  
Growing!