Wolf® Tripod Stands

These tripods let Wolf lamps be positioned at different heights and angles, directing light precisely where needed. They are lightweight, easy to transport, can extend up to 3.5 meters, and support up to 40kg.

Once set up, the tripod provides a stable platform for using LinkEx™ LED Temporary Luminaires, LED Floodlights, and XT Flood Bank Stands at different heights and positions. The tripods allow the lamps to be positioned for vertical or horizontal light, and in the horizontal position, the light can be directed upwards to illuminate the work area from below.

There are two models available:

- **LL-668/35**: Extends up to 3.5 meters and supports up to 40kg.
- **LL-699/18**: A medium-duty tripod that extends up to 1.8 meters.

A mounting bracket is needed to attach the LinkEx[™] LED
Temporary Luminaire and Portable Fluorescent Leadlamp to the tripod, allowing horizontal or vertical positioning. An optional mounting bracket (LL-669 Z bracket) is available for LinkEx[™] LED Floodlights and XT Flood Bank Stands (for Medium and Heavy Duty Tripods) to easily attach and remove the lamp for frequent repositioning at ground level.





PRODUCT REFERENCE		LL-699/18	LL-668/35
PRODUCT DESCRIPTION		Medium Duty Tripod Stand	Heavy Duty Tripod Stand
MATERIAL		Steel plated	Powder coated mild steel, Zinc plated mild steel tube
HEIGHT (EXTENDS TO)		1.8m	3.5m
WIDTH (LEG EXTENSION)		1m	1.38m
WEIGHT		6kg	6.4kg
SUITABLE FOR		LX-400/LX-400(E), WF-250XL, WF-300XL and XT-4XX/6XX Ranges	
MOUNTING BRACKET	LX-400/LX- 400€	LX-670 (L Bracket) LL-670/1 Pipe Clamp	LX-670 (L Bracket) LL-670/1* & LL-670/2 Pipe Clamp (*LL-670/1 Pipe Clamp can only be used on the telescopic section of the LL-668/35 Tripod)
	WF-250XL / WF-300XL	Not Required	LL-669 (optional) Z bracket attached to floodbank/floodlite stands for frequent removal from tripod and repositioning of lamp at ground level.
	XT-4XX / 6 XX	Not Required	



