



Wolf TS 24B-26B Series Safety Torches

Product Code: 08010100

WOLF TS-24B T4 Series Safety Torch (2 Batteries- Straight Angle)
P/N : 08010100

WOLF TS-26B T4 Series Safety Torch (2 Batteries- Right Angle)
P/N : 08010300



TS-24B = I 2GD Ex eb ib IIB T4
Gb

Ex tb IIIC T95°C Db

(-10°C ≤ Ta ≤ +40/55°C)

ATEX certified

TS-26B = II 2GD
Ex eb ib IIB T6
Gb

Ex tb IIIC T65°C
Db

(-10°C ≤ Ta ≤
+40°C)

ATEX
certified

EN 60529:1992 standard IP 67 water and dust protection.

Design:

Suitable for use in Zones 1 & 2
Gas Groups IIB T6 (TS-26B) and
T4 (TS-24B) temperature range.

Suitable for use in Zones 21 &
22 Gas Groups IIC

Xenon filled filament balloon type source provides 1.2 watt illumination.

Shielded reinforced glass lens, impact resistant thermoplastic, electrostatic housing

Operates with 2 pcs 1,5 V.batteries and provides illumination more than 12 hours.

Weight is appr. 150 / 190 grams.



CE Mark



Ex-Proof (ATEX)

TECHNICAL INFORMATION

WOLF TS-24B T4 Series Safety Torch (2 Batteries- Straight Angle) P/N : 08010100

WOLF TS-26B T4 Series Safety Torch (2 Batteries- Right Angle) P/N : 08010300

TS-24B = I 2GD Ex eb ib IIB T4 Gb

Ex tb IIIC T95°C Db

(-10°C ≤ Ta ≤ +40/55°C)

ATEX certified

TS-26B = II 2GD Ex eb ib
IIB T6 Gb

Ex tb IIIC T65°C Db

(-10°C ≤ Ta ≤ +40°C)

ATEX
certified

EN 60529:1992 standard IP 67 water and dust protection.

Design:

Suitable for use in Zones 1 & 2 Gas Groups IIB T6 (TS-26B) and T4 (TS-24B) temperature range.

Suitable for use in Zones 21 & 22 Gas Groups IIC

Xenon filled filament balloon type source provides 1.2 watt illumination.

Shielded reinforced glass lens, impact resistant thermoplastic, electrostatic housing

Operates with 2 pcs 1,5 V.batteries and provides illumination more than 12 hours.

Weight is appr. 150 / 190 grams.

