



## Wolf VF-EFi75xx 30cm Ex-proof Fan



- ATEX and IECEx certified for use in Zone 1 & 2
- Class leading air-flow at up to 2,500 cfm (4,250 m<sup>3</sup>/hr)
- Thermal protection offered by cut-off switch
- Durable, PC/ABS anti-static casing is weatherproof, flame retardant and chemical resistant
- 7.6 metre extended reach power cable
- IP55 water tight rain tested switch enclosure

### Teknik Bilgiler

Product Reference	VF-EFi75xx (115V)	VF-EFi75xx (230V)
Product Description	30cm Hazardous Area Fan / Ventilator	
Code	II 2 G Ex db eb IIB T6 Gb II 2 G Ex h IIB T6 Gb	

Type of Protection	'db' flameproof enclosures  'eb' increased safety  'h' non-electrical equipment	
Area of Class (Gas)	Zones 1 and 2, Gas Groups IIA and IIB	
Max Surface Temp (Gas)	T6	
Ambient Temp. (Gas)	-20°C TO +40°C	
Certificate	DEMKO 09 ATEX 0926969X  IECEX UL 13.0062X	
Enclosure	Anti-static Polycarbonate  ABS Alloy	
Motor	0.75 Hp (0.56 kW)	
Voltage	115V 50/60Hz	230V 50/60Hz
Amps: Start	37A	27A
Amps: Run	8.8A	4.4A
Free Air Through Duct	2,500 cfm (4,250 m <sup>3</sup> /hr)	
15'/4.6m /w one 90° turn:	1,664 cfm (2,829 m <sup>3</sup> /hr)	

15'/4.6m /w two 90° turn:	1,529 cfm (2,599 m <sup>3</sup> /hr)
Ingress Protection	IP55
Dimensions (h/w/d)	41 x 38 x 41 cm
Weight	20kg
Duct Adapters	2
Noise	89db @ 1m



Delivering Worldwide  
**70+** Countries and  
Growing!