



Wolf XT-75 Rechargeable Handlamp

Product Code: 08020150

Suitable for use in Zone 0,1&2 Gas Group IIA, IIB, IIC , T4 temperature range .

2 pcs of powerful white LED illumination source provides lightening up to 12 hours.

Impact-resistant, thermoplastic, electrostatic solidified glass housing.

Lithium-ion battery is fully charged in approximately 3.5-hours. Can be charged and can be used more than 500 times.

Weight is 1.2 Kgs

EN 60529:1992 standard , IP 66 water and dust protection

EX II 1 G Ex ia IIC T4 Ga IP66 ATEX certificate.



TECHNICAL INFORMATION

Suitable for use in Zone 0,1&2 Gas Group IIA, IIB, IIC , T4 temperature range .

2 pcs of powerful white LED illumination source provides lightening up to 12 hours.

Impact-resistant, thermoplastic, electrostatic solidified glass housing.

Lithium-ion battery is fully charged in approximately 3.5-hours. Can be charged and can be used more than 500 times.

Weight is 1.2 Kgs

EN 60529:1992 standard , IP 66 water and dust protection

EX II 1 G Ex ia IIC T4 Ga IP66 ATEX certificate.



SINCE
1979



9001:2015
CERTIFIED
COMPANY



Delivering Worldwide
70+ Countries and
Growing!