



## Emergency Shower and Eye/Face Wash with Overhead



Standard 1500/2000 L Overhead Tank Showers guarantee 15 minutes of water flow according to the standard requirements in bellow circumstances;

1. Without mains (water) supply connection
2. In low water pressure
3. Interruption of flow in existing water supply connection

Different materials (Galvanized Steel, Stainless Steel, GRP) can be used in different system parts as optionally. You can customize your tank shower system by selection guide to integrate the system by chosen desired accessories and various system parts. Water Tanks are insulated. An integral immersion heater or a chiller unit can be added to the system with the options of ex-proof and non ex-proof, in order to keep the water temperature constant between 15-38 °C. Heating and cooling capacities may be changed according to customer requirements. Available in green, yellow or white color

Build and design your emergency tank showers in 3D according to the required climate & area classification!

Search “[Safety Shower Builder](#)” on Apple App Store or click on the link below and stay connected!

<https://apps.apple.com/tr/app/safety-shower-builder/id1536803797?l=tr>



CE Mark



ANSI / ISEA Z358.1-2014



Ex-Proof (ATEX)



EN 15154-3



EAC

## TECHNICAL INFORMATION

---

Standard 1500/2000 lt Overhead Tank Showers guarantee 15 minutes of water flow according to the standard requirements in bellow circumstances;

1. Without mains (water) supply connection
2. In low water pressure
3. Interruption of flow in existing water supply connection

Different materials (Galvanized Steel, Stainless Steel, GRP) can be used in different system parts as optionally. You can customize your tank shower system by selection guide to integrate the system by chosen desired accessories and various system parts. Water Tanks are insulated. An integral immersion heater or a chiller unit can be added to the system with the options of ex-proof and non ex-proof, in order to keep the water temperature constant between 15-38 °C. Heating and cooling capacities may be changed according to customer requirements. Available in green, yellow or white color

Build and design your emergency tank showers in 3D according to the required climate & area classification!

Search “[Safety Shower Builder](#)” on Apple App Store or click on the link below and stay connected!

<https://apps.apple.com/tr/app/safety-shower-builder/id1536803797?l=tr>



SINCE  
1979



9001:2015  
CERTIFIED  
COMPANY



Delivering Worldwide  
70+ Countries and  
Growing!