



## ISTEC TYPE EW Wall-Mounted Stainless Steel Eye/Face Wash

### Product Numbers:

P/N: 15011000 (Stainless Steel)

P/N: 15011000-316 (AISI 316 Stainless Steel)

P/N: 15011500 (Galvanized and Painted Steel)



### The Ideal Solution for a Safe Working Environment

The ISTEC TYPE EW Wall-Mounted Eye/Face Wash is designed to provide rapid and effective intervention during accidental incidents in hazardous work environments. It is manufactured in compliance with ANSI/ISEA Z358.1-2014 and EN 15154-2 standards and is certified accordingly. This product is highly preferred in industries such as chemical, petrochemical, pharmaceutical, food, metal processing, and other sectors.

### Product Features:

**Durable and Aesthetic Design:** ISTEC TYPE EW feature a stainless steel structure, offering durability and an aesthetic appearance. Wall mounting ensures space-saving and maintains order in the workspace.

**Certified for Safe Use:** Our ATEX-certified (explosion-proof) models are available for safe usage in hazardous environments, ensuring full compliance with occupational health and safety standards.

**Manufactured to Standards:** Produced and certified in accordance to ANSI/ISEA Z358.1-2014 and EN 15154-2 standards.

**Optimal Water Temperature Control:** Optional thermostatic valves maintain water temperature between 16-38 °C, maximizing user comfort. By mixing hot and cold water from the mains supply, thermostatic mixing valves achieve the ideal temperature. If the water temperature falls outside this range, please contact our sales team for alternative solutions.



CE Mark



ANSI / ISEA Z358.1-2014



ANSI / ISEA Z358.1-2014  
(Plumbing)



Meets requirements of ANSI  
standard.



EN 15154-2



EAC

## TECHNICAL INFORMATION

### Product Numbers:

**P/N:** 15011000 (Stainless Steel)

**P/N:** 15011000-316 (AISI 316 Stainless Steel)

**P/N:** 15011500 (Galvanized and Painted Steel)

## The Ideal Solution for a Safe Working Environment

The ISTECH TYPE EW Wall-Mounted Eye/Face Wash is designed to provide rapid and effective intervention during accidental incidents in hazardous work environments. It is manufactured in compliance with ANSI/ISEA Z358.1-2014 and EN 15154-2 standards and is certified accordingly. This product is highly preferred in industries such as chemical, petrochemical, pharmaceutical, food, metal processing, and other sectors.

### Product Features:

**Durable and Aesthetic Design:** ISTECH TYPE EW feature a stainless steel structure, offering durability and an aesthetic appearance. Wall mounting ensures space-saving and maintains order in the workspace.

**Certified for Safe Use:** Our ATEX-certified (explosion-proof) models are available for safe usage in hazardous environments, ensuring full compliance with occupational health and safety standards.

**Manufactured to Standards:** Produced and certified in according to ANSI/ISEA Z358.1-2014 and EN 15154-2 standards.

**Optimal Water Temperature Control:** Optional thermostatic valves maintain water temperature between 16-38 °C, maximizing user comfort. By mixing hot and cold water from the mains supply, thermostatic mixing valves achieve the ideal temperature. If the water temperature falls outside this range, please contact our sales team for alternative solutions.



SINCE  
1979



9001:2015  
CERTIFIED  
COMPANY



Delivering Worldwide  
70+ Countries and  
Growing!