



## WOLF LINKEX™ WF-250XL LED FLOODLITE



- Light output, LED:
  - HV 4,334 lumens (at source), 3,189 lumens (emitted)
  - LV 4,224 lumens (at source), 3,065 lumens (emitted)
  - Ideal light output for smaller confined spaces - minimal glare and shadows
  - Highly reliable LEDs
    - Designed and tested to give 100,000+ hours life
    - LED life assured by efficient heat dissipation through built in fins and electronic control
- Effective work area illumination when using a limited power source
  - Up to 8 lights can be connected from one transformer
  - Complementary product to existing range of LinkEx™ LED Temporary Luminaire area lighting system
  - LINKEx capable - both LV and HV units can be fitted with linkable sockets.
- Low power consumption, reduced operating costs:
  - HV 31 watts
  - LV 28 watts
- Enhanced safety:
  - SOVI™ - Wolf's unique Safe Optimal Voltage Indicator system alerts the user if lights are running outside certified and optimal voltage ranges, maximising safety and performance
  - Safe to 0 volts - both LV and HV units are safe down to 0 volts
- Design and construction:
  - Small, lightweight and compact - easy to carry
  - Tough, reliable, proven materials for long life and reduced costs:
    - Marine grade aluminium enclosure
    - Toughened, scratch, impact and chemical resistant glass lens
    - 316 stainless steel frame.
    - Easy to clean, doesn't harbour dirt
    - IP66/67 dust and watertight

## TECHNICAL INFORMATION

---

- Light output, LED:
  - HV 4,334 lumens (at source), 3,189 lumens (emitted)
  - LV 4,224 lumens (at source), 3,065 lumens (emitted)
  - Ideal light output for smaller confined spaces - minimal glare and shadows

- Highly reliable LEDs
  - Designed and tested to give 100,000+ hours life
  - LED life assured by efficient heat dissipation through built in fins and electronic control
- Effective work area illumination when using a limited power source
  - Up to 8 lights can be connected from one transformer
  - Complementary product to existing range of LinkEx™ LED Temporary Luminaire area lighting system
  - LINKEx capable - both LV and HV units can be fitted with linkable sockets.
- Low power consumption, reduced operating costs:
  - HV 31 watts
  - LV 28 watts
- Enhanced safety:
  - SOVI™ - Wolf's unique Safe Optimal Voltage Indicator system alerts the user if lights are running outside certified and optimal voltage ranges, maximising safety and performance
  - Safe to 0 volts – both LV and HV units are safe down to 0 volts
- Design and construction:
  - Small, lightweight and compact - easy to carry
  - Tough, reliable, proven materials for long life and reduced costs:
    - Marine grade aluminium enclosure
    - Toughened, scratch, impact and chemical resistant glass lens
    - 316 stainless steel frame.
    - Easy to clean, doesn't harbour dirt
    - IP66/67 dust and watertight

