

Wolf XT-90 Ex-Proof Rechargeable Handlamp



I M2/II 2GD Ex ib op is I Mb/IIC T4 Gb IP67 Ex ib op is IIIB T185°C Db (Temperature ambient -30°C to +40°C)

Mine: I M2 Ex ib I Mb IP67

It holds an IP67 ATEX certification.

It provides IP67 water and dust protection according to the EN 60529:1992 standard.

Gas groups: Zones 1 and 2, Gas groups: IIA, IIB, and IIC

Gas temperature class: T4

Dust groups: Zone 21 and 22, Dust groups: IIIA and IIIB

Maximum dust temperature class: 185°C

It provides illumination for up to 6 hours with one powerful white LED light source.

It has a solidified glass lens and a body made of impact-resistant thermoplastic with electrostatic protection.

The lithium-ion battery can be charged in approximately 4.5 hours and can be charged and used more than 500 times.

It weighs 1.2 kilograms.

TECHNICAL INFORMATION

I M2/II 2GD Ex ib op is I Mb/IIC T4 Gb IP67 Ex ib op is IIIB T185°C Db (Temperature ambient -30°C to +40°C)

Mine: I M2 Ex ib I Mb IP67

It holds an IP67 ATEX certification.

It provides IP67 water and dust protection according to the EN 60529:1992 standard.

Gas groups: Zones 1 and 2, Gas groups: IIA, IIB, and IIC

Gas temperature class: T4

Dust groups: Zone 21 and 22, Dust groups: IIIA and IIIB

Maximum dust temperature class: 185°C

It provides illumination for up to 6 hours with one powerful white LED light source.

It has a solidified glass lens and a body made of impact-resistant thermoplastic with electrostatic protection.

The lithium-ion battery can be charged in approximately 4.5 hours and can be charged and used more than 500 times.

It weighs 1.2 kilograms.

