FYRAL® 9000

Fire Proximity Suit

P/N : 13303900

EN 1486:2007

MED 2489/23

EN ISO 13688:2022

PPE Personal Protective Equipment Category III REGULATION (EU)2016/425

CE 2777

Outer layer: Aluminized glass fiber
Heat Barrier: 4 Layers of %100 Kermel® Nonwoven
Inner Layer: %65 Lenzing™FR, %22 Teijinconex®, %12 Polyamide, %1 Belltron®

KERMEL LENZING Belltron Teijinconex

*Fyral® is a registered trademark of our company.
*Kermel® is a registered trademark of Kermel SAS.
*Lenzing™FR is a registered trademark of Lenzing AG.
*Belltron® is a registered trademark of Swicofil AG.
*Teijinconex® and Twaron® are registered trademarks of Teijin Aramid B.V.

FYRAL® series aluminized fire proximity suits; The head protects against the harmful effects of high temperature and intense radiant heat, including hands and legs.

Aluminum foil coated aluminized outer layer technology provides high protection against intense radiant heat.

Manufactured in accordance with the new Personal Protective Equipment Regulation (EU) 2016/425.The fire proximity suit is certified according to EN 1486:2007 European standard and carries the CE mark. The design and ergonomics of the suit are in accordance with EN ISO 13688 standard.Protective clothing consists of jackets, trousers, hood with helmet and gold vaporized visor, gaiter with fireman boots and gloves.
Coat : It is suitable for internal breathing apparatus. It has a zipper in the front, there is a velcro on the zipper.
Hood with visor : It is detachable from the coat, has a panoramic view and protects the neck, chest and shoulder areas.
Trousers: The suspenders are adjustable, the cuffs have elastic.
Gloves: There are 5 finger gloves from its own layer.
Leggings: It is in accordance with EN 15090 and EN ISO 20345 standard. Firefighter boots are sold with their aluminized sheath.
All parts of the suits are made of the same layer system as the suits.
The suit is sold as a set with a special carrying bag.
FYRAL® 9000 suits are composed of below parts:
Hood with visorJacket with expanded back for breathing apparatus
Fire proof closure elements are located on front of the jacket.

Complementary Products

3M SCOTT SIGMA-II TYPE 2

BODY SIZES

	Body	Length	Chest	Waist
S	(46 / 48)	164-170	**88-96**	109
M	(50 / 52)	170-176	**96-104**	112
L	(54 / 56)	176-182	**104-112**	115
XL	(58 / 60)	182-188	**112-120**	118
XXL	(62 / 64)	188-194	**120-128**	121

Tolerance +2

İŞÇİ SAĞLIĞI TEÇHİZATI
IST Safety Ltd
www.ist.com.tr

İvedik OSB Mh. 2269. Cd.
No: 42 Yenimahalle 06374,
Ankara, TÜRKİYE

Tel:+90 312 384 13 00 Pbx
info@ist.com.tr
www.ist.com.tr

Scan the QR code with your phone's camera to review the product on our website and get an offer.