

FYRAL®

850V

P/N : 13075210

Industrial Aluminized Aluminized Open Back Coat Against Raidant Heat and Molten Metal Splash



The FYRAL® 850V Protective Aluminized Foundry Open Back Coat for Radiant Heat and Molten Metal Splash provides superior protection against the effects of high heat, flames, molten metal splashes, and intense radiant heat in the casting and metalworking industries.

Key Features

Radiant Heat and Molten Metal Splash Protection: Offers enhanced safety providing protection against high heat, flames, molten metal splashes, and radiant heat.

Ergonomic Design

Provides comfortable movement with an ergonomic structure compliant with EN ISO 13688 standards.

Comfortable to Use

Designed as a open back coat, made with aluminized viscose fabric for maximum protection. It is lightweight and easy to wear.



EN ISO 11612
A1 B1 C3 D3
E3 F1



Outer layer: Aluminized Viscose FR
Layer system: Single-layer

PERFORMANCE CLASS EN ISO 11612

EN ISO 15025 - LIMITED FLAME SPREAD	A1
ISO 9151 - CONVECTIVE HEAT	B1
EN ISO 6942 - RADIANT HEAT	C3
ISO 9185 - MOLTEN ALUMINUM SPLASH	D3
ISO 9185 - MOLTEN IRON SPLASH	E3
ISO 12127 - CONTACT HEAT	F1



İŞÇİ SAĞLIĞI TEÇHİZATI
www.ist.com.tr

İvedik OSB Mh. 2269. Cd.
No: 42 Yenimahalle 06374,
Ankara, TÜRKİYE

Tel:+90 312 384 13 00 Pbx
info@ist.com.tr
www.ist.com.tr

Scan the QR code with your phone's camera to review the product on our website and get an offer.