SHOWERS & EYEBATHS

Human disinfection tunnel provides an effective sanitation and helps to reduce bacterial and viral infection risks.

The system operates automatically by its sensors when the user enters inside the tunnel.

Sanitation continues for 10 seconds.

After a 10-second operating time, the aerators (spray nozzles) stop spraying and the user leaves the tunnel.

24 months limited warranty and wooden cases are included.

Frame Material

Accessories

Disinfection

Dimensions (WxLxH)

Electrical Power Supply

Side Cabin Panels (Standard)

Weight of the cabinet is 25 kgs Weight of the water tank and pump is 52 kgs

Spray Nozzles

Water Hose

Water Tank

Pump

Accessories of pump and water tank room



Disinfection chemicals are provided by the end-user.
Our company does not accept responsibility
for the chemicals to be used.



Water level indicator and junction box

40 L 316SS or 100 L Plastic

100x100x210 cm

220V 50 Hz

40 L 316SS or 100 L Plastic

100x100x210 cm

220V 50 Hz

HUMBN DISINFE

SHOWERS & EYEBATHS



- 1 Disinfection Chemical Options*: Hydrogen Peroxide & Colloidal Silver & Chlorinated Water
- Frame Material Options: Aluminium Sigma & Steel
- Floor Options: Empty & GRP Grating & Carpet
- Side Cabin Panel Options: Polycarbonate & Galvanized and Painted Steel & Stainless Steel & GRP
- Water Tank Options: 316 Stainless Steel 40 L & Plastic 100 L
- PVC Curtain at the entrance and exit
- Internal lighting with proximity swtich
- B Junction Box
- White GRP Sun Canopy
- Special labelling


*Chemicals are provided by the end-user.
Our company does not accept responsibility
for the chemicals to be used.

*Photos are shown as example. Actual items may appear differently.

PLEASE ASK FOR YOUR SPECIAL REQUIREMENTS



TECHNICAL DRAWING





We provide variety of special services you may need.

Engineering Consultation

IST provides complete information on the design, use, supply and care of emergency showers and eye/face washes & decontamination units & disinfection tunnels.

For all your needs during a new plant installation or facility renovation, our experienced team will guide you to the best and most economical solution.

Quality and Safe Product Selection

Our product range has a wide range of standard and optional designs. For interior and exterior applications, we offer high quality systems with heating or cooling, with freeze protection, portable or fixed special systems.

Special Engineering Solutions

Each unit is designed for different purposes and cannot substitute each other. In addition, standardized units with heating or cooling, may not always be the right choice for your needs. IST is fully equipped to offer and produce the special designed systems according to your needs.

Adjusting Water Temperature

Tepid water supply (16 – 38 ° C), which is a requirement of both American and European standards, requires special attention. Our expert team has the capability to analyze resources of your facility and offer solutions to ensure that emergency showers and eye / face wash fountains will work properly under all circumstances.

Our experts will work in coordination with your design or expert team.

Pre-Sales Solid Modelling and Technical Drawing

We provide customized design and engineering solutions to customers with our advanced three-dimensional solid modelling software. In this way, our customers can more easily analyze the suitability of the product to their facility and can plan the project accordingly.

Two or three dimensional detailed technical drawings are available for all our products.

After-Sales Support

Our expert technicians can evaluate your existing systems to ensure compliance with ANSI and EN Standards.

Our expert team will assist you about training and product setup for your new unit.

All our products are guaranteed against production and workmanship defects for a period of 24 months.



2 +90 312 384 13 00

+90 312 341 73 03





www.ist.com.tr